
MinificationWebHelpers Documentation

Release 0.3.6

Pedro Algarvio & Domen Kozar

October 15, 2011

CONTENTS

Author Pedro Algarvio <ufs_REMOVE@ME_ufsoft.org>

Maintainer Domen Kozar <domen_REMOVE@ME_dev.si>

Version 0.3.6

Source bitbucket.org

Bug tracker bitbucket.org/issues

Consider the [MinificationWebHelpers](#) an extension to [WebHelpers](#).

Basically [MinificationWebHelpers](#) adds following options to the [WebHelpers](#) [javascript_link](#) and [stylesheet_link](#) functions:

- **minified** (bool): Minifies/reduces as much as possible each of the files passed to it's minimum size to reduce page load times.
- **combined** (bool): Joins all files passed into a single one to reduce server requests which in turn reduces page load times.
- **beaker_kwargs** (dict): override default arguments that will be passed to *beaker_cache*.
- **combined_filename** (string): Name of the filename that will be used in conjunction with *combined=True*

For complete list of additional parameters refer to `base_link()`.

Note: Running Pylons/TG application in debug mode will force minified and combined options off.

Note: For an up-to-date read of the documentation, always refer to [official documentation page on site](#).

DETAILS ABOUT IMPLEMENTATION

`MinificationWebHelpers` cache your javascript and css files through `Beaker`'s `@beaker.cache` decorator. Default parameters passed to beaker cache:

```
beaker_kwargs = dict(key='sources', expire='never', type='memory')
```

Javascript minification is achieved through Python port of `jsmin`.

`MinificationWebHelpers` maps HTTP URLs to filesystem path by examining pylons config for *static_files*.

USAGE

On your own [Pylons](#) application, inside `<app>/lib/helpers.py` you add:

```
from minwebhelpers import *
```

Then, inside a template you could have:

```
<head>
    ${ h.javascript_link('/js/file1.js',
                        '/js/file2.js',
                        minified=True,
                        combined=True,

    ${ h.stylesheet_link('/css/style1.css',
                        '/css/style2.css',
                        minified=True,
                        combined=True,
                        beaker_kwargs=dict(invalidate_on_startup=False)) }

</head>
```

combin

The above would mean `file1.js` and `file2.js` would be combined and then minimized (same story for css files).

INSTALATION

It's as easy as:

```
sudo easy_install MinificationWebHelpers
```

Or if you wish to install current trunk:

```
sudo easy_install http://bitbucket.org/iElectric/minificationwebhelpers/get/tip.zip
```


API

CHANGELOG

5.1 17-04-2010: Domen Kozar v0.3.6

- added *strip_prefix* parameter to `minwebhelpers.base_link()`

5.2 28-09-2009: Domen Kozar v0.3.5

- added *timestamp* parameter [thanks to bobf]

5.3 10-06-2009: Domen Kozar v0.3.4

- finally refactored custom `cssutils` serializer, threw out some stuff and fixed bugs.

5.4 10-06-2009: Domen Kozar v0.3.3

- fix compatibility with Windows platform (`os.path`)

5.5 09-06-2009: Domen Kozar v0.3.2

- added *combined_filename* parameter
- fixed a bug when two paths were similar and resulted in `IOError`

5.6 22-05-2009: Domen Kozar v0.3.1

- updated documentation
- added *beaker_kwargs* option to both function that overrides default caching behaviour
- fixed a bug when paths were not joined correctly
- written unittests

5.7 04-05-2009: Domen Kozar v0.3.0

- fixed a bug when sources were not invalidated (in cache) on startup
- complete refactoring

5.8 16-04-2009: Domen Kozar v0.2.1

- replaced deprecated rails functions with new webhelpers.html package
- added `invalidate_on_startup=True` argument to `beaker.cache`

5.9 02-02-2007: Pedro Algarvio v0.2.0

- Included the fix implemented on [110], wasn't included on trunk.
- Skip minification/combination when requesting builtin javascripts.

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

PYTHON MODULE INDEX

m

minwebhelpers, ??